

NEW HOBO MX2300 Series Loggers

*Bluetooth (BLE) Weatherproof loggers
for outdoor temperature and humidity
measurements*

With Onset's new HOBO MX2300 Series Temp/RH loggers, field data collection has never been easier. You can set up and offload loggers wirelessly from your mobile device – eliminating the need to take a laptop or data shuttle into the field to retrieve data.



Key Advantages:

- Weatherproof housing for use in outdoor or condensing environments
- High-accuracy measurements
- RH sensor provides superior recovery from condensing conditions
- Small-diameter, external sensor versions for measurements in tight spaces
- Wireless setup & download with Bluetooth Low Energy (BLE)

Supported Measurements:

Temperature, Relative Humidity, Dew Point

Minimum System Requirements:



Choice of Models

The HOBO MX2300 Series offers five models covering a broad range of outdoor monitoring applications, from agricultural research to forest ecology studies. The series includes internal sensor models that are highly durable and easy to deploy, and external probe models that are well-suited for monitoring conditions in soils, water, walls, and more.

Part number	MX2301 (Internal Temp/RH)	MX2302 (External Temp/RH)	MX2303 (2x External Temp)	MX2304 (External Temp)	MX2305 (Internal Temp)
Temperature Sensor					
Range	-40 to 70°C (-40 to 158°F)		-40 to 100°C (-40 to 212°F) with tip and cable immersion in fresh water up to 50°C (122°F) for one year		-40 to 70°C (-40 to 158°F)
Accuracy	±0.25°C from -40 to 0°C (±0.45 from -40 to 32°F) ±0.2°C from 0 to 70°C (±0.36 from 32 to 158°F) ±0.25°C from 70 to 100°C (±0.45 from 158 to 212°F), MX2303 and MX2304 only				
Resolution	0.04°C (0.072°F)				
Drift	<0.01°C (0.018°F) per year				
Relative Humidity Sensor (MX2301, MX2302 only)					
Range	0 to 100% RH, -40° to 70°C (-40° to 158°F); exposure to conditions below -20°C (-4°F) or above 95% RH may temporarily increase the maximum RH sensor error by an additional 1%				
Accuracy	±2.5% from 10% to 90% (typical) to a maximum of ±3.5% including hysteresis at 25°C (77°F); below 10% RH and above 90% RH: ±5% typical				
Resolution	0.05%				
Drift	<1% per year typical				
Logger					
Memory	128 KB (84,650 measurements, maximum)				
Operating Range	-40° to 70°C (-40° to 158°F), IP67 and NEMA#6				
Transmission Range	Approximately 30.5 m (100 ft) line-of-sight				
Logging Rate	1 second to 18 hours				
Dimensions	Logger housing: 10.8 x 5.08 x 2.24 cm (4.25 x 2.0 x 0.88 in.)				
Mobile Device Compatibility	iOS 8.3, 8.4 & 9.0, and Bluetooth 4.0 or later				
CE compliant	Yes				

PLEASE SEE MX2302A BROCHURE FOR UPDATED SPECIFICATIONS ON THE MX2301A and MX2302A

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- ▶ Email sales@onsetcomp.com
- ▶ Call 1-508-759-9500
- ▶ In U.S. toll free 1-800-564-4377
- ▶ Fax 1-508-759-9100

Technical Support (8am to 8pm ET, Monday through Friday)

- ▶ Contact Product Support onsetcomp.com/support/contact
- ▶ Call 1-508-759-9500
- ▶ In U.S. toll free 1-877-564-4377

Onset Computer Corporation
470 MacArthur Boulevard
Bourne, MA 02532

